

HD-TVI CAMERA

5MP IR Fisheye Camera

VHC-5540



Technical Specifications

Model No	VHC-5540
Image Sensor	5MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	2592 (H) × 1944 (V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter speed	1/12.5s to 1/20,000s
Lens	1.1mm
Lens Mount	M12
Angle Adjustment	Pan: 0°-30°; Tilt: 0°; Rotate: 0°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	5MP @ 12.5 fps
HD Video Output	1 Analog HD output
Audio In	Built-in Mic
Audio Out	1-ch, BNC Output, (Output Impedance: 1KΩ)
Mounting Type	Ceiling/Wall
Ceiling Mounting Display Mode	Default, Panorama, 4 PTZ, Fisheye & 3 PTZ, Annular Mini-fisheye & 1 PTZ, Annular & 2 PTZ
Wall Mounting Display Mode	Default, Panorama, 4 PTZ, Fisheye & 3 PTZ, Panorama & 3 PTZ
D/N Mode	Color/BW/AUTO
Functions	Brightness, contrast, saturation, sharpness
Working Temperature	-40°C ~ +60°C
Humidity	90% or less (non-condensing)
Power Supply	12 VDC±30%
Power Consumption	Max. 6W
IR Range	Up to 10-20m
Communication	Up the coax
Dimensions	164 x 152.8 x 43.8mm (6.46" x 6.02" x 1.72")
Weight	Approx. 1500 g

Key Features

- 5 Megapixel high-performance CMOS
- Analog HD output, up to 5MP resolution
- 1.1mm fish eye lens
- IR cut filter with auto switch
- True Day/Night
- Built-in microphone
- OSD menu, DNR, SMART IR
- UTC (Up the Coax) function

Dimensions

