

## EXIR HD-TVI CAMERA

### 5MP EXIR Turret Camera

#### VHC-5560



#### Key Features

- 5 Megapixel high-performance CMOS
- Analog HD output, up to 5MP resolution
- 2.8mm, 3.6mm, 6mm fixed lens
- EXIR technology, up to 20m IR distance
- True Day/Night
- OSD menu, DNR, SMART IR
- UTC (Up the Coax) function
- IP67 weatherproof

#### Technical Specifications

Model No	VHC-5560
Image Sensor	5MP CMOS Image Sensor
Effective Pixels	2592 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm, 6 mm fixed focal Lens
Angle of View	86.5° (2.8 mm), 70.1° (3.6 mm), 46° (6 mm)
Lens Mount	M 12
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 75°; Rotate: 0° to 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	2592 × 1944 @ 20fps
HD Video Output	1 Analog HD output
S / N Ratio	> 62dB
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/MWB
BLC	Support
Functions	Brightness, Sharpness, Digital noise reduction, Mirror Bad pixel correction, Smart IR
Working Temperature	-40°C ~ +60°C
Humidity	90% or less (non-condensing)
Power Supply	12 VDC±30%
Power Consumption	Max. 5W
Weather Proof Ratings	IP 67
IR Range	Up to 20m
Communication	Up the coax
Dimensions	91 mm × 82.6 mm × 68.3 mm (3.58" × 3.25" × 2.69")
Weight	Approx. 350 g (0.77 lb)

#### Dimensions

